





Section I. C.	Section I. Chemical Product and Company Identification					
Product Name	PURITY FG00	Code	650-106, PFG00			
		DSL	See Section 15			
Synonym	Not available	TSCA	See Section 15			
Manufacturer	PETRO-CANADA P.O. Box 2844 Calgary, Alberta T2P 3E3	In case of Emergency	Petro-Canada: 403-296-3000 , Canutec Transportation: 613-996-6666 Poison Control Centre:			
Material Uses	NSF H1 Registered. This product complies with FDA requirements for "Lubricants with Incidental Food Contact". It is intended for application on industrial and food equipment. It should not be added directly to the food product.		Consult local telephonidirectory for emergenc number(s).			

Section II. Composition and Information on Ingredients						
				Expos	ure Limits (ACGIH)	
Name CAS # % (Wt)			TLV-TWA(8 h)	STEL	CEILING	
White oil and proprietary additives.		Mixture	100	Not established	Not established	Not established
Manufacturer Recommendation	This product is not expected to form a mist based on its properties and expected use.					
Other Exposure Limits Consult local, state, provincial or territory authorities for acceptable exposure limits.						

•			
Section	Ш	Hazards	Identification

Potential Health Effects

Prolonged or repeated contact may cause skin irritation, defatting, drying and dermatitis. Not expected to cause more than slight skin or eye irritation. With its relatively low vapour pressure, this product is not expected be inhaled in any appreciable quantity at ambient conditions. If heated to high temperatures or subjected to mechanical actions which produce vapours or mists, inhalation may cause respiratory tract irritation. Ingestion may produce a laxative effect. For more information refer to Section 11 of this MSDS.

Section IV. Fi	rst Aid Measures
Eye Contact	No effects expected. If irritation does occur, flush contaminated eye(s) with lukewarm, gently flowing water for 5 minutes or until the chemical is removed. If irritation persists, obtain medical advice.
Skin Contact	Quickly and gently, blot or brush away excess chemical. Wash gently and thoroughly with water and non-abrasive soap for 5 minutes or until chemical is removed. Remove contaminated clothing, shoes and leather goods (e.g., watchbands, belts, etc.). If irritation persists, repeat flushing. Obtain medical advice immediately. Completely decontaminate clothing, shoes and leather goods before reuse or discard.
Inhalation	Remove source of contamination or move victim to fresh air. If irritation persists, obtain medical advice.
Ingestion	NEVER give anything by mouth if victim is rapidly losing consciousness, or is unconscious or convulsing. DO NOT INDUCE VOMITING. Have victim drink 240 to 300 mL (8 to 10 oz) of water to dilute material in stomach. If vomiting occurs naturally, rinse mouth and repeat administration of water. Obtain medical attention.
Note to Physician	Not available

Flammability	May be combustible at high temperature.	Flammable Limits	Not available
Flash Points	Open cup: 249°C (480°F) (Cleveland)	Auto-Ignition Temperature	Not available
Fire Hazards in Presence of Various Substances	Low fire hazard. This material must be heated before ignition will occur.	Explosion Hazards in Presence of Various Substances	Do not cut, weld, heat, drill or pressurize empty container. Containers may explode in heat of fire.
Products of Combustion	Carbon oxides (CO, CO2), smoke and irritating vapours as products of incomplete combustion.		

Continued on Next Page Internet: www.petro-canada.ca/msds Available in French

PURITY FG00 Page Number: 2

Fire Fighting Media and Instructions

NAERG2004, GUIDE 171, Substances (low to moderate hazard). If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (0.5 mile) in all directions; also, consider initial evacuation for 800 meters (0.5 mile) in all directions. Shut off fuel to fire if it is possible to do so without hazard. If this is impossible, withdraw from area and let fire burn out under controlled conditions. Withdraw immediately in case of rising sound from venting safety device or any discolouration of tank due to fire. Cool containing vessels with water spray in order to prevent pressure build-up, autoignition or explosion. SMALL FIRE: use DRY chemicals, foam, water spray or CO2. LARGE FIRE: use water spray, fog or foam. For small outdoor fires, portable fire extinguishers may be used, and self contained breathing apparatus (SCBA) may not be required. For all indoor fires and any significant outdoor fires, SCBA is required. Respiratory and eye protection are required for fire fighting personnel.

Section VI. Accidental Release Measures

Material Release or Spill

Consult current National Emergency Response Guide Book (NAERG) for appropriate spill measures if necessary. Ensure clean-up personnel wear appropriate personal protective equipment. Extinguish all ignition sources. Stop leak if safe to do so. Dike spilled material. Use appropriate inert absorbent material to absorb spilled product. Collect used absorbent for later disposal. Avoid contact with spilled material. Avoid contaminating sewers, streams, rivers and other water courses with spilled material. Notify appropriate authorities immediately.

Section VI	Section VII. Handling and Storage				
Handling	Avoid contact with any sources of ignition, flames, heat, and sparks. Avoid eye contact. Avoid skin contact. Avoid inhalation of product vapours or mists. Wear proper personal protective equipment (See Section 8). Empty containers may contain product residue. Do not pressurize, cut, heat, or weld empty containers. Do not reuse containers without commercial cleaning and/or reconditioning. Personnel who handle this material should practice good personal hygiene during and after handling to help prevent accidental ingestion of this product. Properly dispose of contaminated leather articles including shoes that cannot be decontaminated.				
Storage	Store away from incompatible and reactive materials (See section 5 and 10). Keep container tightly closed. Store in dry, cool, well-ventilated area.				

Section VIII. Exposure Controls/Personal Protection

work-station.

Engineering Controls For normal application, special ventilation is not necessary. If user's operations generate vapours or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit. Make-up air should always be supplied to balance air removed by exhaust ventilation. Ensure that eyewash station and safety shower are close to

Personal Protection - The selection of personal protective equipment varies, depending upon conditions of use.

Eves As a minimum, safety glasses with side shields should be worn when handling this material.

Body If this material may come in contact with the body during handling and use, we recommend wearing appropriate protective clothing to prevent contact with the skin. (Contact your PPE provider for more information.)

Respiratory A minimum of NIOSH-approved air-purifying respirator with an organic vapour cartridge or canister with a dust, fume of mist filter (R, or P series) may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air-purifying respirators is limited. A NIOSH-approved positive-pressure, air-supplied respirator or self-contained breathing apparatus may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits.

Hands If this material may come in contact with the hands during handling and use, we recommend wearing gloves of the following material(s): neoprene, nitrile, polyvinyl alcohol (PVA), fluoro-elastomer. Consult your PPE provider for breakthrough times and the specific glove that is best for you based on your use patterns. It should be realized that eventually any material regardless of their imperviousness, will get permeated by chemicals. Therefore, protective gloves should be regularly checked for wear and tear. At the first signs of hardening and cracks, they should be changed.

Feet Wear appropriate footwear to prevent product from coming in contact with feet and skin.

Section IX. Physical and Chemical Properties				
Physical State and Appearance	Semi-solid.	Viscosity	Mineral Oil Blend: 182 cSt @ 40°C, 17 cSt @ 100°C, VI=99	
Colour	White.	Pour Point	Mineral Oil Blend: -15°C (5°F)	
Odour	Bland.	Softening Point	Not available	
Odour Threshold	Not available	Dropping Point	≥149°C	
Boiling Point	>371°C (699.8°F)	Penetration	400-430 (60 strokes)	
Specific Gravity	Mineral Oil Blend: 0.8770 kg/L @ 15°C (59°F).	Oil / Water Dist. Coeff	f.Not available	
Vapour Density	Not available	Ionicity (in water)	Not available	
Vapour Pressure	Negligible at ambient temperature and pressure.	Dispersion Properties	Not available	
Volatility	Not available	Solubility	Insoluble in water.	

Section X. Stability and Reactivity			
Corrosivity	Non corrosive.		
Stability	The product is stable under normal handling and storage conditions.	Hazardous Polymerization	Will not occur under normal working conditions.
Incompatible Substances / Conditions to Avoid	Reactive with oxidizing agents.	Decomposition Products	May release COx, SOx, NOx, smoke and irritating vapours when heated to decomposition.

Page Number: 3

PURITY FG00

Section XI. Toxicologica	I Information
Routes of Entry	Skin contact, eye contact, inhalation and ingestion.
Acute Lethality	Not available
Chronic or Other Toxic Effects Dermal Route:	Prolonged or repeated contact may defat and dry skin, and cause dermatitis. Short-term exposure is expected to cause only slight irritation, if any.
Inhalation Route:	With its relatively low vapour pressure, this product is not expected be inhaled in any appreciable quantity at ambient conditions. If heated to high temperatures or subjected to mechanical actions which produce vapours or mists, inhalation may cause respiratory tract irritation.
Oral Route:	Ingestion of this product may lead to aspiration of the liquid, especially if vomiting occurs. This may result in chemical pneumonitis (inflammation of the lungs) and/or pulmonary edema (an accumulation of fluid in the lungs). May produce a laxative effect.
Eye Irritation/Inflammation:	Short-term exposure is expected to cause only slight irritation, if any.
Immunotoxicity:	Not available
Skin Sensitization:	Contact with this product is not expected to cause skin sensitization, based upon the available data and the known hazards of the components.
Respiratory Tract Sensitization:	Contact with this product is not expected to cause respiratory tract sensitization, based upon the available data and the known hazards of the components.
Mutagenic:	This product is not known to contain any components at >= 0.1% that have been shown to cause mutagenicity. Therefore, based upon the available data and the known hazards of the components, this product is not expected to be a mutagen.
Reproductive Toxicity:	This product is not known to contain any components at >= 0.1% that have been shown to cause reproductive toxicity. Therefore, based upon the available data and the known hazards of the components, this product is not expected to be a reproductive toxin.
Teratogenicity/Embryotoxicity:	This product is not known to contain any components at >= 0.1% that have been shown to cause teratogenicity and/or embryotoxicity. Therefore, based upon the available data and the known hazards of the components, this product is not expected to be a teratogen/embryotoxin.
Carcinogenicity (ACGIH):	This product is not known to contain any chemicals at reportable quantities that are listed as Group A1 or A2 carcinogens by ACGIH.
Carcinogenicity (IARC):	This product is not known to contain any chemicals at reportable quantities that are listed as Group 1, 2A, or 2B carcinogens by IARC.
Carcinogenicity (NTP):	This product is not known to contain any chemicals at reportable quantities that are listed as carcinogens by NTP.
Carcinogenicity (IRIS):	This product is not known to contain any chemicals at reportable quantities that are listed as carcinogens by IRIS.
Carcinogenicity (OSHA):	This product is not known to contain any chemicals at reportable quantities that are listed as carcinogens by OSHA.
Other Considerations	No additional remark.

Section XII. Eco	ological Information		
Environmental Fate	Not available	Persistance/ Bioaccumulation Potential	Not available
BOD5 and COD	Not available	Products of Biodegradation	Not available
Additional Remarks	No additional remark.		

Section XIII. D	Disposal Considerations
Waste Disposal	Spent/ used/ waste product may meet the requirements of a hazardous waste. Consult your local or regional authorities. Ensure that waste management processes are in compliance with government requirements and local disposal regulations.

PURITY FG00 Page Number: 4

Section XIV. Transport Information

DOT Classification

Not a hazardous material for transport | Special Provisions according to the requirements of the DOT. (United States)

for Transport

Not applicable.

Section XV. Regulatory Information

Other Regulations

This product is acceptable for use under the provisions of WHMIS-CPR. All components of this formulation are listed on the CEPA-DSL (Domestic Substances List).

All components of this formulation are listed on the US EPA-TSCA Inventory.

All components of this formulation are listed on EINECS or are exempt.

German Water Hazard Classification (Verwaltungsvorschrift wassergefährdende Stoffe - VwVwS) WGK=1

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

Please contact Product Safety for more information.

DSD/DPD (EEC)

Not classified under the Dangerous Substances or Dangerous Preparations Directives

WHMIS (Canada) Not controlled

ADR (Europe) (Pictograms)



TDG (Canada) (Pictograms)



Section XVI. Other Information

References

Available upon request.

* Marque de commerce de Petro-Canada - Trademark

Glossarv

ACGIH - American Conference of Governmental Industrial Hygienists ADR - Agreement on Dangerous goods by Road (Europe)

ASTM - American Society for Testing and Materials

BOD5 - Biological Oxygen Demand in 5 days CAS - Chemical Abstract Services

CEPA - Canadian Environmental Protection Act

CERCLA - Comprehensive Environmental Response, Compensation

and Liability Act

CFR - Code of Federal Regulations

CHIP - Chemical Hazard Information and Packaging Approved Supply List

COD - Chemical Oxygen Demand

CPR - Controlled Products Regulations

DOT - Department of Transportation (U.S.A.)

DSCL - Dangerous Substances Classification and Labeling (Europe) DSD/DPD - Dangerous Substance or Dangerous Preparations Directives (Europe)

DSL - Domestic Substance List (Canada)

EEC/EU - European Economic Community/European Union

EINECS - European Inventory of Existing Commercial Chemical

EPCRA - Emergency Planning And Community Right-To-Know Act

FDA - Food and Drug Administration

FIFRA - Federal Insecticide, Fungicide, and Rodenticide Act

HCS - Hazardous Communication System

HMIS - Hazardous Material Information System IARC - International Agency for Research on Cancer

IRIS - Integrated Risk Information System

LD50/LC50 - Lethal Dose/Concentration kill 50%

LDLo/LCLo - Lowest Published Lethal Dose/Concentration

NFPA - National Fire Prevention Association

NIOSH - National Institute for Occupational Safety & Health NPRI - National Pollutant Release Inventory

NSNR - New Substances Notification Regulations (Canada)

NTP - National Toxicology Program

OSHA - Occupational Safety & Health Administration

PEL - Permissible Exposure Limit

RCRA - Resource Conservation and Recovery Act

SARA - Superfund Amendments and Reorganization Act

STEL - Short Term Exposure Limit (15 minutes)

TDG - Transportation Dangerous Goods (Canada) TDLo/TCLo - Lowest Published Toxic Dose/Concentration

TLV-TWA - Threshold Limit Value-Time Weighted Average

TLm - Median Tolerance Limit

TSCA - Toxic Substances Control Act

USEPA - United States Environmental Protection Agency

USP - United States Pharmacopoeia

WHMIS - Workplace Hazardous Material Information System

Information Contact

The Canadian Controlled Products Regulations (CPR) (Under the Hazardous Products Act, part of the WHMIS legislation) only apply to WHMIS Controlled (i.e., hazardous) products. Therefore, the CPR and the 3-year update rule specified therein do not apply to WHMIS Non-Controlled products. Although this is true, customarily Petro-Canada reviews and updates Non-Controlled product MSDS if a customer requests such an update. These Non-Controlled product updates are given a lower priority than Controlled products but are handled as soon as practicable. If you would like to verify if the MSDS you have is the most current, or you require any further information, please contact:

Prepared by Product Safety - JDW on 9/7/2007.

Data entry by Product Safety - DSR.

Lubricants:

Continued on Next Page

Western Canada, telephone: (001) 1-800-661-

1199; fax: (001) (780) 464-9564

Ontario & Central Canada, telephone: (001) 1-

Internet: www.petro-canada.ca/msds

Available in French

PURITY FG00	Page Number: 5
800-268-5850 and (001) (905) 822-4222; fax: (001) 1-800-201-6285 Quebec & Eastern Canada, telephone: (001) 1-800-576-1686; fax: (001) 1-800-201-6285	
For Product Safety Information: (905) 804-4752	

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.